



JET CONNECTIVITY
Extending Horizons

JET5G-R

Camera-Spec

SA/NSA Router

Tailored to seamlessly integrate into diverse system architectures, the **JET5G-R** ensures industry 4.0 connectivity in even the most challenging environments. Offering robust, multi-channel hybrid communication capability with versatile support for various data types.

The **JET5G-R** is your gateway to next-level connectivity, offering the flexibility to deploy as part of a Fixed Wireless Access (FWA) solution without additional infrastructure, while sustaining reliability. Supplied with a camera module and a rechargeable battery pack, for extended compatibility and integration with drones.



Multi-channel
High Bandwidth

Versatile 5G
Connectivity

Secure &
Reliable



www.jet-eng.co.uk

JET5G-R (Camera Spec) Specifications

General Specification

| | |
|--------------------------|-----------------------------|
| Model Number | JET5G-1003 |
| Available Colours | Available on request |
| Physical Dimensions (mm) | 192 (l) x 127 (w) x 136 (h) |
| Mass (kg) | 1.7 |

Communications - 5G

| | |
|-------|--|
| 5G NR | 3GPP Release 15 NSA/SA Operation Sub-6 Ghz |
| NSA | n38, n41, n77, n78, n79 |
| SA | n1, n2, n3, n5, n7, n8, n12, n20, n38, n40, n41, n48* n66, n77, n78, n79 |
| MIMO | DL: 4x4 MIMO on n1, n2, n3, n7, n25, n38, n40, n41, n48, n66, n77, n78, n79 UL: 2x2 MIMO on n4, n77, n78, n79 |

Communications - LTE

| | |
|--------------|---|
| LTE Category | DL Cat 16 / UL Cat 18 |
| LTE-TDD | B34, B38, B39, B40, B41, B42, B43, B48 |
| LTE-FDD | B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B20, B25, B26, B28, B29, B30, B23, B66, B71 |
| LAA | B46 |
| MIMO | DL: 4x4 MIMO on B1, B2, B3, B4, B7, B25, B30, B34, B38, B39, B40, B41, B42, B43 B48, B66 |

Connectivity

| | |
|-------------------|--|
| WiFi + LAN (RJ45) | 5G SA: Sub-6 DL 2.1 Gbps; UL 900 Mbps 5G NSA: Sub-6 DL 2.5 Gbps; UL 650 LTE DL: 1.0 Gbps; UL 200 Mbps WCDMA: DL 42 Mbps; UL 5.76 Mbps |
|-------------------|--|

Hardware Specification

| | |
|-------------------|--|
| Processor | Broadcom BCM2711, Quad-core Cortex-A72 |
| Memory (RAM) | 4GB LPDDR4-3200 SDRAM |
| Wireless Module | UK/US/EU Proprietary Modules - POA |
| CAN BUS Interface | Waveshare RM500Q-GL |
| Integrated Camera | 8MP IMX219 Autofocus Camera Module |



JET5G-R (Camera Spec) Specifications Cont.

Interfaces

| | |
|----------------|-------------------------|
| External Data | 1 x USB-A 3.0, 1 x RJ45 |
| Antenna Ports | 4 x SMA |
| SIM Card Slots | Nano SIM |
| Power Port | PELR0142 |

Power & Environmental

| | |
|------------------------|---------------|
| Power Input | 5V 3A |
| Operating Temperature* | -10° to +45°C |
| IP Rating* | IP67 |
| Battery | 26800mAh |

*Designed to meet

